

PC 43

FEATURES

TECHNICAL DATA

Plasma Torch
Input Voltage
Power 60%
U _s
Amp. min-max
Duty Cycle 40°C
Severance
Quality cutting
Air pressure
Air Capacity
Insulation
Protection degree
Dimens. (LxWxH)
Box (LxWxH)
Weight box/net

PC 43

PT40
(1ph) 230V ± 10% · 50/60Hz
3,3 KVA
350 V
15 ÷ 40 A
40A @ 20% 25A @ 60% 20A @ 100%
15 mm
13 mm
4 - 5 bar
100 l/min
H
IP22S
155x430x320 mm
260x560x355 mm
11,8 / 10,8 kg

STANDARD CONFIGURATION

Part number	Description	
99830019	PC 43	
43210150	Ground cable · Fixed · 6mm ² · 4,0 m	INCLUDED
23010070	Plasma torch PT40 · Fixed · 4,0 m	
23015224	Plasma consumable · Contact Tip · Ø 0,9 mm · 30-40 A	
23015186	Plasma consumable · Contact Tip · Ø 0,8 mm · 20-30 A	
23015189	Plasma consumable · Contact Tip · Ø 0,65 mm · 10-20 A	
23015187	Plasma consumable · Electrode	