

PC COMBI 302K
FEATURES

TECHNICAL DATA

Plasma Torch
Input Voltage
U ₀
Power 60%
Amp. min-max
Duty Cycle 40°C
Severance
Air pressure
Air Capacity
Insulation
Protection degree
Dimens. (LxWxH)
Box (LxWxH)
Weight box/net

PC COMBI 302K

PT40C	
(1ph) 230V ± 10% · 50/60Hz	
310 V	
Internal Compressor	External Air
2,5 KVA	3,0 KVA
12 ÷ 25 A	12 ÷ 28 A
25A @ 40% 12A @ 100%	28A @ 30% 12A @ 100%
8 mm	10 mm
-	4,5 bar
-	100 l/min
H	
IP22S	
200x435x395 mm	
290x560x400 mm	
20,4 / 19,0 kg	

STANDARD CONFIGURATION

Part number	Description	
99830015	PC COMBI 302K	
43210150	Ground cable · Fixed · 6mm ² · 4,0 m	INCLUDED
23010067	Plasma torch PT40C · Fixed · 4,0 m	
23015186	Plasma consumable · Contact Tip · Ø 0,8 mm · 20-30 A	
23015189	Plasma consumable · Contact Tip · Ø 0,65 mm · 10-20 A	
23015187	Plasma consumable · Electrode	
23015188	Plasma consumable · Nozzle · 6 holes (for external compressor)	