

NOVA 191NEN 60974-6
EN 60974-10

MMA



MMA

ENG • Single-phase AC portable welding units. Stepless control of the welding current. Thermostatic overload protection.

IT • Saldatrici ad elettrodo, portatili, monofasi, in corrente alternata. Regolazione lineare della corrente di saldatura. Protezione termostatica.

ES • Máquinas de soldar con electrodos, portátiles, monofásicas, de corriente alterna. Regulación lineal de la intensidad de soldadura. Protección con termostato.

DEU • Tragbare Lichtbogenschweißmaschinen, einphasig, Wechselstrom. Lineare Regulierung des Schweißstroms. Thermostatischer Schutz.

FR • Postes à souder portables, monophasés, à courant alternatif. Réglage continu du courant de soudage. Protection thermostatique.

RU • Однофазный переносной сварочный аппарат переменного тока. Плавное регулирование сварочного тока, защита от тепловых перегрузок.

NOVA 191N	
Input Voltage	(1ph) 230/400V 50/60Hz
Power 60%	4 KVA
U_o	48 V
Amp. Min-Max	35 ÷ 170 A±10%
Ø E	1,6 ÷ 4 mm
Insulation	H
Protec. Degree	IP21S
Dimens. (LxWxH)	500x255x350 mm
Box (LxWxH)	550x280x365 mm
Weight box/net	19,6 / 18,5 Kg
Code	99200081