

# GALILEO 219



## FEATURES



## TECHNICAL DATA

Input Voltage
Power 60%
U <sub>o</sub>
Amp. min-max
Duty Cycle 40°C
Ø Electrode
Electrode Type
Insulation
Protection degree
Dimens. (LxWxH)
Weight box/net

GALILEO 219	
	(1ph) 230V ± 10% · 50/60Hz
	6 KW
	48 V
	10 ÷ 200 A
	200A @ 60% 155A @ 100%
	1,6 ÷ 5 mm
	6013 - 7018
	H
	IP23S
	140x360x255 mm
	7,4 / 6,8 Kg

## STANDARD CONFIGURATION

Part number	Description
99806009	GALILEO 219

99806011	GALILEO 219 + HELVI BAG KIT	300x530x345 mm · 12,6 / 11,5 Kg
99806009	Power Source · Galileo 219	INCLUDED
43210170	Ground cable · 25mm <sup>2</sup> · 2,0 m	
43205097	Welding cable · 25mm <sup>2</sup> · 3,0 m	
21905178K	Helvi Bag M · 450x220x270 mm	

## OPTIONAL

Part number	Description	
99900278	KIT CABLES 25mm <sup>2</sup>	
43210170	Ground cable · 25mm <sup>2</sup> · 2,0 m	INCLUDED
43205097	Welding cable · 25mm <sup>2</sup> · 3,0 m	