

GALILEO TIG 219 HF

FEATURES

TECHNICAL DATA

Input Voltage
Power 60%
U _o
Amp. min-max
Duty Cycle 40°C
Ø Electrode
Electrode Type
Insulation
Protection degree
Dimens. (LxWxH)
Box (LxWxH)
Weight box/net

GALILEO TIG 219 HF

(1ph) 230V ± 10% · 50/60Hz		
TIG	MMA	
4,2 KW	5,3 KW	
64 V	64 V	
5 ÷ 200 A	5 ÷ 160 A	
200A @ 20%	160A @ 20%	
115A @ 60%	95A @ 60%	
90A @ 100%	75A @ 100%	
-	1,6 ÷ 4 mm	
-	6013 - 7018	
H		
IP23S		
140x400x245 mm		
175x510x290 mm		
8,8 / 8,2 Kg		

STANDARD CONFIGURATION

Part number	Description
99806005	GALILEO TIG 219 HF

99806007	GALILEO TIG 219 HF + HELVI BAG KIT	300x620x325 mm · 15,8 / 14,7 Kg
99806005	Power Source · Galileo TIG 219 HF	INCLUDED
43210170	Ground cable · 25mm² · 2,0 m	
23020157	TIG torch · Ergotig 26 · 50mm² · 4,0 m · 3 pin	
3090030	Gas hose KIT · 2,0 m	
21905133	TIG welding gloves · Size 10	
21905139K	Helvi Bag XL · 540x225x250 mm	