

TP 195A



INCLUDED

- 23000424 · MIG Torch · 15AK · 3m
- 43210138 · Ground Cable · 2m · 16mm²
- 22905090 · Pressure Regulator ECO mini CO₂
- 22910014 · Gas bottle adaptor
- 33805003 · Drive roll · Ø30 mm · 0,6 ÷ 0,8 mm

OPTIONAL

- 23020173 · TIG Torch · 17V · 4m

TP 195A			
Input Voltage	(1ph) 230V ± 10% 50/60Hz		
Power 60%	2,3 KVA		
	MMA	TIG	MIG
U ₀	70 V	70 V	70 V
Amp. Min-Max	20 ÷ 180 A	5 ÷ 180 A	25 ÷ 180 A
Duty Cycle 40°	180A @ 20% 105A @ 60% 75A @ 100%	180A @ 20% 105A @ 60% 75A @ 100%	180A @ 20% 105A @ 60% 75A @ 100%
Ø Steel	-	-	0,6 ÷ 1,0 mm
Ø Flux core	-	-	0,9 mm
Ø Stainless Steel	-	-	0,8 ÷ 1,0 mm
Ø Aluminium	-	-	0,8 ÷ 1,0 mm
Ø Brazing	-	-	0,8 ÷ 1,0 mm
Ø E	1,6 ÷ 3,25 mm	-	-
Electrode type	6031 - 7018 - CrNi		
Insulation	H		
Protec. degree	IP22S		
Dimens. (LxWxH)	770x465x660 mm		
Box (LxWxH)	795x360x540 mm		
Weight box/net	36 / 32 Kg		
Code	99820057		