

SPARC 226



FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
U _o
Amp. min-max
Duty Cycle 40°C
Ø Electrode
Electrode Type
Insulation
Protection degree
Dimens. (LxWxH)
Weight box/net

SPARC 226	
	(1ph) 230V ± 10% · 50/60Hz
	3,2 KW
	70 V
	20 ÷ 200 A
	200A @ 25% 130A @ 60% 100A @ 100%
	1,6 ÷ 4,0 mm
	6013 - 7018
	H
	IP22S
	120x285x255 mm
	3,9 / 4,4 Kg

STANDARD CONFIGURATION

Part number	Description
99805993	SPARC 226

99806003	SPARC 226 + CARTON BOX KIT	245x385x235 mm · 7,6 / 7,0 Kg
99805993	Power Source · Sparc 226	INCLUDED
43210236	Ground cable · 16mm ² · 2,0 m	
43205114	Welding cable · 16mm ² · 3,0 m	
21905064	Welding mask · Glass 75x98 mm	
44900001	Glass KIT	
21905039	Hammer/Brush	

99806013	SPARC 226 + HELVI BAG KIT	300x530x345 mm · 8,6 / 7,8 Kg
99805993	Power Source · Sparc 226	INCLUDED
43210236	Ground cable · 16mm ² · 2,0 m	
43205114	Welding cable · 16mm ² · 3,0 m	
21905039	Hammer/Brush	
21905178K	Helvi Bag · 450x220x270 mm	