



PUMA 298



INCLUDED

Power Supply	99825016 400V (No accessories)
MIG Torch	23000350 · Ergoplus 25 · 3m
Ground cable	43210142 · 35mm ² · 3m
Pressure regulator	22905049 mini CO ₂ /Argon · 2 manometers
Adaptor for gas bottles	22910014

	PUMA 298		
Input Voltage	(3ph) 400V ± 10% 50/60Hz		
	MIG	MMA (only Rutile)	TIG
Power 60%	6 KW	6 KW	5,8 KW
U _o	35 V	54 V	54 V
Amp. Min-Max	30 ÷ 290 A	20 ÷ 250 A	10 ÷ 280 A
Duty Cycle 40°	290A @ 35%	250A @ 35%	290A @ 35%
Ø Steel	0,8 ÷ 1,0 mm	-	-
Ø Stainless Steel	0,8 ÷ 1,0 mm	-	-
Ø Aluminium	1,0 ÷ 1,2 mm	-	-
Ø Flux core	1,0 ÷ 1,2 mm	-	-
Ø CuSi ₃	0,8 mm	-	-
Ø E	-	1,6 ÷ 5 mm	-
Electrode Type	-	6013 Rutile	-
Insulation	H		
Protection degree	IP23		
Dim. (LxWxH)	450x840x710 mm		
Box (LxWxH)	365x895x650 mm		
Weight box/net	37 / 35 Kg		
Part number	99825016K		

PUMA 
MIG INVERTER RANGE