

# GALILEO TIG 211 EASY AC/DC



## FEATURES



## TECHNICAL DATA

<b>Input Voltage</b>
<b>Power 60%</b>
<b>U<sub>0</sub></b>
<b>Amp. min-max</b>
<b>Duty Cycle 40°C</b>
<b>Ø Electrode</b>
<b>Electrode Type</b>
<b>Insulation</b>
<b>Protection degree</b>
<b>Dimens. (LxWxH)</b>
<b>Box (LxWxH)</b>
<b>Weight box/net</b>

## GALILEO TIG 211 EASY AC/DC

(1ph) 110V ± 10% · 50/60Hz			(1ph) 230V ± 10% · 50/60Hz		
TIG		MMA	TIG		MMA
DC	AC	DC	DC	AC	DC
2 KW	2 KW	2,2 KW	2,3 KW	2,5 KW	4 KW
45 V	45 V	45 V	45 V	45 V	45 V
5 ÷ 140 A	10 ÷ 140 A	5 ÷ 100 A	5 ÷ 200 A	10 ÷ 200 A	5 ÷ 170 A
140A 40%	140A 40%	100A 35%	200A 25%	200A 30%	170A 30%
110A 60%	110A 60%	75A 60%	130A 60%	140A 60%	120A 60%
85A 100%	85A 100%	60A 100%	100A 100%	110A 100%	90A 100%
-	-	1,6 ÷ 2,5 mm	-	-	1,6 ÷ 5 mm
-	-	6013 - 7018	-	-	6013 - 7018
H					
IP23S					
195x490x395 mm					
300x640x455 mm					
12,0 / 11,2 Kg					

## STANDARD CONFIGURATION

Part number	Description	
<b>99806020</b>	<b>GALILEO TIG 211 EASY AC/DC</b>	
22105166	Male connetor for TIG torch · 12 pins	INCLUDED
<b>99806020K</b>	<b>GALILEO TIG 211 EASY AC/DC + KIT</b>	<b>340x630x460 mm · 21,2 / 19,6 Kg</b>
99806020	Power Source · Galileo TIG 211 EASY AC/DC	INCLUDED
43210170	Ground cable · 25mm² · 2,0 m	
23020410	TIG torch · Tig 26 · 50mm² · 4,0 m · 12 pin	
3090030	Gas hose KIT · 2,0 m	

## OPTIONAL

Part number	Description
23020410	TIG torch · Tig 26 · 50mm² · 4,0 m · 12 pin
99900258	Trolley
99810021	Foot remote control · 12 pin · 5,0 m