

mini FOX 161

FEATURES

TECHNICAL DATA

| |
|-------------------|
| Input Voltage |
| Power 60% |
| U _o |
| Amp. min-max |
| Duty Cycle 40°C |
| Steel |
| Flux Core |
| Insulation |
| Protection degree |
| Dimens. (LxWxH) |
| Box (LxWxH) |
| Weight box/net |

| mini FOX 161 | |
|----------------------------|--|
| (1ph) 230V ± 10% · 50/60Hz | |
| 2 KW | |
| 26 V | |
| 10 ÷ 150 A | |
| 150A @ 20% | |
| 90A @ 60% | |
| 70A @ 100% | |
| 0,8 Ø mm | |
| 0,9 Ø mm | |
| H | |
| IP22S | |
| 190x370x335 mm | |
| 250x580x355 mm | |
| 10,0 / 9,2 Kg | |

STANDARD CONFIGURATION

| Part number | Description | |
|-----------------|---|----------|
| 99820060 | mini FOX 161 | |
| 23000142K | MIG torch · fixed · 10mm ² · 2,0 m | INCLUDED |
| 43210234 | Ground cable · 10mm ² · 2,0 m | |
| 21910116 | Flux core wire spool · 0,5 Kg · Ø 0,9 mm | |
| 30900030 | Gas hose KIT · 2,0 m | |
| 33805074 | Drive roll · Ø 25 mm · 0,6 ÷ 0,8/0,9 mm · Knurled | |
| 21905039 | Hammer Brush | |