

UNITECH PULSE 350C



FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
U _o
Amp. min-max
Duty Cycle 40°C
Insulation
Protection degree
Dimens. (LxWxH)
Weight box/net

UNITECH PULSE 350C

(3ph) 400V ± 10% · 50/60Hz

	MIG	MMA	TIG
Power	12,1 KVA*	10,3 KVA*	9,4 KVA*
U _o	45 V*	60 V*	12 V*
Amp. min-max	30 ÷ 350 A*	20 ÷ 320 A*	5 ÷ 350 A*
Duty Cycle 40°C	350A @ 45%* 300A @ 60%* 250A @ 100%*	320A @ 45%* 270A @ 60%* 240A @ 100%*	350A @ 45%* 300A @ 60%* 250A @ 100%*
Insulation	H		
Protection degree	IP 23S		
Dimens. (LxWxH)	440x930x840 mm		
Weight box/net	-		

STANDARD CONFIGURATION

Part number	Description	
99825018K	UNITECH PULSE 350C · H ₂ O	
99825018	Power source	INCLUDED
99490032K	Cooler unit UNITECH C + tank CL 500 · 5 kg	
33805140	Pressure roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) ●●	
33805145	Drive roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) ●●	

*the data are preliminary and may change in the future