

PP 29W

FEATURES


Input cable NOT INCLUDED
Optional external water cooling

TECHNICAL DATA

Input Voltage	
Power 50%	
Delayed fuses	
Min arm projection	
Max arm projection	
Electrode force	
Max welding capacity	
Ø Arms	
Dimens. (LxWxH)	
Weight box/net	

PP 29W

(3ph) 400V ± 10% · 50/60Hz
25 KVA
45 A
260 mm
500 mm
275 daN (6 bar)
3 + 3 mm
45 mm
441x852x1260 mm
131,0 / 125,0 kg

STANDARD CONFIGURATION

Part number	Description
9950512K	Power Source PP 29W

CUSTOMIZED CONFIGURATION
GRUPPI DI RAFFREDDAMENTO

99490021KA	Cooler unit SMART 230V 220AC/DC + tank CL 500 · 5 kg
99490027KA	Cooler unit SMART 400V + tank CL 500 · 5 kg
10910035	Tank CL 500 · 5 kg
10910036	Tank CL 500 · 25 kg

COPPIA BRACCI RAFFREDDATI · RICAMBI

99920510	CB-80 · Pair of cooled arms with Ø 45x500 mm / electrode holders · Ø 20x185 mm / cone · Ø 12
99920511	CB-90 · Pair of cooled arms with Ø 45x700 mm / electrode holders · Ø 20x185 mm / cone · Ø 12
99920512	CB-90 ITD · Pair of cooled arms with Ø 45x700 mm / lower straight head · Ø 20 mm
99920513	CB-90 ITI · Pair of cooled arms with Ø 45x700 mm / lower angled head · Ø 20 mm
99920514	PE-8/185 · Pair of cooled arms with electrode holders without electrode · Ø 20x185 mm
99920515	PE-8/300 · Pair of cooled arms with electrode holders without electrode · Ø 20x300 mm

ELETTRODI · RICAMBI

99920516	E-53/8 · No center electrode · 20 pcs
99920517	E-54/8 · Central point head · 20 pcs
99920518	E-52/8 · Electrode with flexible kneecap · Ø 22 mm · 5 pcs
99920519	E-55/8 · Electrode with flexible kneecap · Ø 30 mm · 5 pcs
99920520	E-60/8 · Flat electrode · Ø 30 mm · 5 pcs
99920521	E-100 · Printed electrode tip with cap · 30 pcs