

UNITECH EVO 358C



FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
U_o
Amp. min-max
Duty Cycle 40°C
Insulation
Protection degree
Dimens. (LxWxH)
Weight box/net

UNITECH EVO 358C		
(1ph) 230V ± 10% · 50/60Hz		
MIG	MMA	TIG
12,1 KVA	10,3 KVA	9,4 KVA
45 V	60 V	12 V
30 ÷ 350A	20 ÷ 300 A	10 ÷ 350 A
350A @ 50% 320A @ 60% 280A @ 100%	300A @ 50% 280A @ 60% 250A @ 100%	350A @ 50% 320A @ 60% 280A @ 100%
H		
IP 23S		
440x930x840 mm		
56,0 / 53,0 kg		

STANDARD CONFIGURATION

Part number	Description	
99825015	UNITECH EVO 358C	
33805101	Drive roll · Ø 30 mm · 0,8 - 1,0 mm	INCLUDED

Part number	Description	
99825019K	UNITECH EVO 358C	
99825015	Power source	INCLUDED
99490032K	Cooler unit UNITECH + tank CL 500 · 5 kg	
33805101	Drive roll · Ø 30 mm · 0,8 - 1,0 mm	