

UNITECH PULSE 360



FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
U _o
Amp. min-max
Duty Cycle 40°C
Insulation
Protection degree
Dimens. (LxWxH)
Weight box/net

UNITECH PULSE 360

(3ph) 400V ± 10% · 50/60Hz		
MIG	MMA	TIG
12,1 KVA	10,3 KVA	9,4 KVA
45 V	60 V	12 V
30 ÷ 350A	20 ÷ 320 A	5 ÷ 350 A
350A @ 45% 300A @ 60% 250A @ 100%	320A @ 45% 270A @ 60% 240A @ 100%	350A @ 45% 300A @ 60% 250A @ 100%
H		
IP 23S		
Power source		445x930x935 mm
Wire feeder		240x570x460 mm
-		

STANDARD CONFIGURATION

Part number	Description	
99855040K	UNITECH PULSE 360 + XP4 LCD · Air	
99850012	Power source NO LCD · Air	INCLUDED
99420081	Wire feeder XP4 LCD · H ₂ O	
99900286	Wheels KIT X4 / H4 / XP4	
44890342	Interconnection cable · 70 mm² · 5 mt · H ₂ O	
99490035K	KIT Cooler unit UNITECH PULSE + tank CL 500 · 5 kg	
33805140	Pressure roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) ●●	
33805145	Drive roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) ●●	