

UNITECH PULSE 500



FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
U _o
Amp. min-max
Duty Cycle 40°C
Insulation
Protection degree
Dimens. (LxWxH)
Weight box/net

UNITECH PULSE 500

(3ph) 400V ± 10% · 50/60Hz		
MIG	MMA	TIG
22,3 KVA*	21 KVA*	16,4 KVA*
45 V*	60 V*	12 V*
30 ÷ 500A*	20 ÷ 500 A*	5 ÷ 500 A*
500A @ 50%*	500A @ 50%*	500A @ 50%*
450A @ 60%*	450A @ 60%*	450A @ 60%*
390A @ 100%*	390A @ 100%*	390A @ 100%*
H		
IP 23S		
Power source 445x930x935 mm		
Wire feeder 240x570x460 mm		
-		

STANDARD CONFIGURATION

Part number	Description	
99855021K	UNITECH PULSE 500 + XP4 LCD · H ₂ O	
99850011	Power source NO LCD	INCLUDED
99420081	Wire feeder XP4 LCD · H ₂ O	
99900286	Wheels KIT X4 / H4 / XP4	
44890342	Interconnection cable · 70 mm² · 5 mt · H ₂ O	
99490035K	KIT Cooler unit UNITECH PULSE + tank CL 500 · 5 kg	
33805140	Pressure roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) ● ●	
33805145	Drive roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) ● ●	

*the data are preliminary and may change in the future