


TP 210



FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
No load voltage U_0
Amp Min-Max
Duty Cycle 40°
Insulation class
Protection degree
Dimensions (LxWxH)
Weight box/net

TP 210		
(1ph) · 230V ± 10% · 50/60 Hz		
7 KVA		
MIG	MMA	TIG
35 V	65 V	65 V
20 ÷ 200 A	5 ÷ 200 A	5 ÷ 200 A
200A @ 35%	200A @ 35%	200A @ 35%
140A @ 100%	120A @ 100%	120A @ 100%
H		
IP 22S		
250x530x400 mm		
23 / 21 kg		

STANDARD CONFIGURATION

Part number	Description	
99820058KA	TP 210	
99820058A	Power source	INCLUDED
33805003	Drive roll · Ø 30 mm · 0,6 - 0,8 mm	
33805104	Drive roll for aluminium · Ø 30 mm · 0,8 - 1,0 mm	
04600706	Accessories KIT for TP 210	
23000494	MIG torch · TRAFIMET ERGO PLUS 25 · 3 mt	
43205098	Welding cable with electrode holder · 16 mm² · 3 mt	
43210132	Ground cable · 25 mm² · 3 mt	
22905090	Pressure regulator 2 gauges · mini ECO	
22910014	Adaptor for gas bottle CO ₂ /Argon	