

PUMA 278



FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
U _o
Amp. min-max
Duty Cycle 40°C
Steel
Stainless steel
Aluminium
Flux Core
CuSi ₃
Insulation
Protection degree
Dimens. (LxWxH)
Box (LxWxH)
Weight box/net

PUMA 278

(3ph) 400V ± 10% · 50/60Hz
4,8 KW
MIG
30 V
30 ÷ 250A
250A @ 30%
190A @ 60%
150A @ 100%
0,8 ÷ 1,0 Ø mm
0,8 ÷ 1,0 Ø mm
1,0 ÷ 1,2 Ø mm
1,0 ÷ 1,2 Ø mm
0,8 Ø mm
H
IP23S
450x840x710 mm
365x895x650 mm
32 / 30 Kg

STANDARD CONFIGURATION

Part number	Description
99825017A	PUMA 278

99825017KA	PUMA 278 + KIT	
99825017A	Power source · Puma 278	INCLUDED
23000494	ErgoPlus MIG 25 · Euro connection · 3,0 m	
43210253	Ground cable · 25mm² · 3,0 m	
33805101	Drive roll · Ø 30 mm · 0,8 ÷ 1,0 mm	
22905049	Pressure regulator · mini CO ₂ /Argon · 2 manometers	
22910014	Adaptor for gas bottle	