

UNITECH PULSE 350C



FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
U _o
Amp. min-max
Duty Cycle 40°C
Insulation
Protection degree
Dimens. (LxWxH)
Weight box/net

UNITECH PULSE 350C

(3ph) 400V ± 10% · 50/60Hz		
MIG	MMA	TIG
18,1 KVA*	14 KVA*	15,6 KVA*
45 V*	60 V*	12 V*
30 ÷ 350 A*	20 ÷ 300 A*	10 ÷ 350 A*
350 A @ 50%*	320 A @ 50%*	350 A @ 50%*
320 A @ 60%*	280 A @ 60%*	320 A @ 60%*
280 A @ 100%*	250 A @ 100%*	280 A @ 100%*
H		
IP 23S		
440x930x840 mm		
-		

STANDARD CONFIGURATION

Part number	Description	
99825018K	UNITECH PULSE 350C · H ₂ O	
99825018	Power source	INCLUDED
99490032K	Cooler unit UNITECH C + tank CL 500 · 5 kg	
33805140	Pressure roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) ●●	
33805145	Drive roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) ●●	

*the data are preliminary and may change in the future