


FOX 185

FEATURES



TECHNICAL DATA

Input Voltage	(1ph) 115V · 50/60Hz	(1ph) 230V · 50/60Hz
Power 60%	1,9 KVA	2,8 KVA
U ₀	60 V	80 V
Amp. min-max	25 ÷ 120 A	20 ÷ 100 A
Duty Cycle 40°C	120A 40% 100A 60% 75A 100%	110A 40% 90A 60% 70A 100%
Steel	0,6 ÷ 0,8 Ø mm	
Stainless steel	0,8 Ø mm	
Aluminium	0,8 ÷ 1,0 Ø mm	
Flux Core	0,9 Ø mm	
CuSi ₃	0,8 Ø mm	
Ø Electrode	1,6 ÷ 3,25 Ø mm	
Electrode type	6013 - 7018 - CrNi	
Insulation	H	
Protection degree	IP22S	
Dimens. (LxWxH)	220x480x385 mm	
Box (LxWxH)	260x590x435 mm	
Weight box/net	16 / 12 Kg	

FOX 185

	(1ph) 115V · 50/60Hz			(1ph) 230V · 50/60Hz		
	1,9 KVA			2,8 KVA		
	MIG	MMA	TIG	MIG	MMA	TIG
U ₀	60 V	80 V	9,5 V	60 V	80 V	9,5 V
Amp. min-max	25 ÷ 120 A	20 ÷ 100 A	5 ÷ 110 A	25 ÷ 170 A	20 ÷ 170 A	5 ÷ 170 A
Duty Cycle 40°C	120A 40% 100A 60% 75A 100%	100A 40% 85A 60% 65A 100%	110A 40% 90A 60% 70A 100%	170A 25% 110A 60% 85A 100%	170A 25% 110A 60% 85A 100%	170A 25% 110A 60% 85A 100%
Steel	0,6 ÷ 0,8 Ø mm					
Stainless steel	0,8 Ø mm					
Aluminium	0,8 ÷ 1,0 Ø mm					
Flux Core	0,9 Ø mm					
CuSi ₃	0,8 Ø mm					
Ø Electrode	1,6 ÷ 3,25 Ø mm					
Electrode type	6013 - 7018 - CrNi					
Insulation	H					
Protection degree	IP22S					
Dimens. (LxWxH)	220x480x385 mm					
Box (LxWxH)	260x590x435 mm					
Weight box/net	16 / 12 Kg					

STANDARD CONFIGURATION

Part number	Description	
99820039A	FOX 185	INCLUDED
23000491	MIG torch 15 · Euro connection · 3,0 m	
43210138K	Ground cable · 16mm ² · 2 m	
21910108	Wire reel · Steel SG2 · 1,0 Kg · Ø 0,8 mm	
30900030	Gas hose KIT · 2 m	
33805003	Drive roll · Ø 30 mm · 0,6 ÷ 0,8 mm	

OPTIONAL

Part number	Description
99900171A	Trolley
43205028K	MMA welding cable · 16mm ² · 3,0 m
23020173	TIG torch Tig 17V · with gas valve · conn. 25mm ² · KIT consumables Ø 1,6 mm