

# UNITECH MMA EVO 418



## FEATURES

							*On Demand

## TECHNICAL DATA

Input Voltage	
Power 60%	
No load voltage $U_0$	
Amp. Min-Max	
Duty Cycle 40°	
Insulation class	
Protection degree	
Dimensions (LxWxH)	
Weight box/net	

## UNITECH MMA EVO 418

400V ± 10% · 50/60 Hz · (3ph)
<b>MMA</b>
12,5 KVA
60 V
20 ÷ 350 A
350A @ 60%
310A @ 100%
H
IP 23S
250x610x440 mm
31,8 / 30,16 kg

## STANDARD CONFIGURATION

Part number	Description
99850009A	UNITECH EVO 418

## CUSTOMIZED CONFIGURATION

### ● MMA WELDING KIT

99900022	MMA Welding KIT · 50 mm <sup>2</sup> · 5+3 mt · conn. 50 mm <sup>2</sup>
99900063	MMA Welding KIT · 70 mm <sup>2</sup> · 5+3 mt · conn. 70 mm <sup>2</sup>

### ● GROUND CABLES

43210076K	Ground cable with clamp · 50 mm <sup>2</sup> · 3 mt · conn. 50 mm <sup>2</sup>
43210115K	Ground cable with clamp · 70 mm <sup>2</sup> · 3 mt · conn. 70 mm <sup>2</sup>
43210247K	Ground cable with C-clamp · 70 mm <sup>2</sup> · 5 mt · conn. 95 mm <sup>2</sup>

### ● WELDING TORCHES

43205037K	Welding cable with electrode holder · 50 mm <sup>2</sup> · 5 mt · conn. 50 mm <sup>2</sup>
43205052K	Welding cable with electrode holder · 70 mm <sup>2</sup> · 5 mt · conn. 70 mm <sup>2</sup>

23020176	TIG Torch · <b>EXPERTIG 26</b> · 4 mt · conn. 50 mm <sup>2</sup> · 12 Pin · Air · Consumables KIT Ø 2,4 mm
----------	--

### ● TROLLEYS

99900171A	Trolley · 2 wheels + shelves <b>ECO</b>
99900258A	Trolley · 4 wheels + shelves <b>HD</b> <span style="float: right;">*(no H<sub>2</sub>O)</span>