

TP 220 EVO

FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
No load voltage U_0
Amp Min-Max
Duty Cycle 40°
Insulation class
Protection degree
Dimensions (LxWxH)
Weight box/net

TP 220 EVO

(1ph) · 230V ± 10% · 50/60 Hz		
MIG	MMA	TIG
7,6 KVA	8,6 KVA	6,0 KVA
35 V	65 V	65 V
20 ÷ 200 A	20 ÷ 200 A	5 ÷ 200 A
200A @ 35%	200A @ 35%	200A @ 35%
160A @ 60%	150A @ 60%	150A @ 60%
140A @ 100%	120A @ 100%	120A @ 100%
H		
IP 22S		
230x400x400 mm		
17,8 Kg		

STANDARD CONFIGURATION

Part number	Description
99820064	TP 220 EVO
33805003	Drive roll · Ø 30 mm · 0,6 - 0,8 mm

Part number	Description
99820064K	TP 220 EVO
99820064	Power source
43210142K	Ground cable with clamp · 35 mm ² · 3 mt · conn. 50 mm ²
23000484	Torch ERGOPLUS 25 · 3 mt · Air
ALU KIT	· Contact tip · Ø 1,0 mm · M8 · AL
	· Swirl ring · M8
	· Wire liner · Ø 1,0 - 1,2 mm · 3,5 mt · Graphite · Grey · brass terminal
	· Brass wire inlet tube · Ø 4,4 x 5 mm · L = 150 mm
33805003	Drive roll · Ø 30 mm · 0,6 - 0,8 mm
33805104	Drive roll for aluminium · Ø 30 mm · 0,8 - 1,0 mm