

# UNITECH EVO 418



## FEATURES



## TECHNICAL DATA

Input Voltage
Power 60%
No load voltage $U_0$
Amp Min-Max
Duty Cycle 40°
Insulation class
Protection degree
Dimensions (LxWxH)
Weight box/net

## UNITECH EVO 418

(3ph) · 400V ± 10% · 50/60 Hz		
MIG	MMA	TIG
14,9 KVA	12,5 KVA	9,8 KVA
45 V	60 V	12 V
30 ÷ 400 A	20 ÷ 350 A	10 ÷ 350 A
400A @ 60% 310A @ 100%	350A @ 60% 310A @ 100%	350A @ 60% 310A @ 100%
H		
IP 23S		
Power source	250x610x440 mm	
Wire feeder	240x560x460 mm	
Cooler Unit	250x600x230 mm	
Trolley	460x1000x800 mm	
86 / 80,05 kg		

## STANDARD CONFIGURATION

99855014KA	UNITECH EVO 418 + X4 SYNERGIC · Air
99850009A	Power source
99420079A	Wire feeder X4 · Air
99900286	Wheels KIT X4 / H4 / XP4
99490031	Lifter KIT Trolley UNI · only Air
44890397	Interconnection cable · 70 mm² · 5 mt · Air
33805140	Pressure roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange)
33805145	Drive roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange)
99900282	Trolley · 4 wheels UNI