

UNITECH EVO 558

FEATURES



TECHNICAL DATA

Input Voltage
Power 60%
No load voltage U_0
Amp Min-Max
Duty Cycle 40°
Insulation class
Protection degree
Dimensions (LxWxH)
Weight box/net

UNITECH EVO 558

(3ph) · 400V ± 10% · 50/60 Hz		
MIG	MMA	TIG
24,6 KVA	21 KVA	16,4 KVA
45 V	60 V	12 V
30 ÷ 550 A	20 ÷ 500 A	10 ÷ 500 A
550A @ 45% 500A @ 60% 400A @ 100%	500A @ 60% 400A @ 100%	500A @ 60% 400A @ 100%
H		
IP 23S		
Power source	250x610x440 mm	
Wire feeder	240x560x460 mm	
Cooler unit	250x600x230 mm	
Trolley	460x1000x800 mm	
91 / 85,05 kg		

STANDARD CONFIGURATION

Part number	Description
99855012KA	UNITECH EVO 558 + X4 SYNERGIC · H ₂ O
99850008A	Power source
99420079A	Wire feeder X4 · H ₂ O
99900286	Wheels KIT X4 / H4 / XP4
99490030KA	Cooler unit SMART XL + tank CL 500 · 5 kg
44890386A	Interconnection cable · 70 mm ² · 5 mt · H ₂ O
33805140	Pressure roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange)
33805145	Drive roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange)
99900282	Trolley · 4 wheels UNI