

UNITECH PULSE 500
FEATURES


NEW
MIG · LCD remote control Unitech Pulse


TECHNICAL DATA

| |
|-----------------------|
| Input Voltage |
| Power 60% |
| No load voltage U_0 |
| Amp Min-Max |
| Duty Cycle 40° |
| Insulation class |
| Protection degree |
| Dimensions (LxWxH) |
| Weight box/net |

UNITECH PULSE 500

| (3ph) · 400V ± 10% · 50/60 Hz | | |
|-------------------------------|-------------|----------------|
| MIG | MMA | TIG |
| 26,3 KVA | 19,3 KVA | 26 KVA |
| 45 V | 60 V | 12 V |
| 30 ÷ 500 A | 20 ÷ 500 A | 5 ÷ 500 A |
| 500A @ 50% | 500A @ 50% | 500A @ 50% |
| 450A @ 60% | 450A @ 60% | 450A @ 60% |
| 390A @ 100% | 390A @ 100% | 390A @ 100% |
| H | | |
| IP 23S | | |
| Power source | | 445x930x935 mm |
| Wire feeder | | 240x570x460 mm |
| 98,1 / 94,2 Kg | | |

STANDARD CONFIGURATION

| Part number | Description |
|------------------|--|
| 99855021K | UNITECH PULSE 500 + XP4 LCD · H₂O |
| 99850011 | Power source NO LCD |
| 99490035K | KIT Cooler unit UNITECH PULSE + tank CL 500 · 5 kg |
| 99420081 | Wire feeder XP4 LCD · H ₂ O |
| 99900286 | Wheels KIT X4 / H4 / XP4 |
| 44890342 | Interconnection cable · 70 mm ² · 5 mt · H ₂ O |
| 33805140 | Pressure roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) |
| 33805145 | Drive roll · Ø 37 mm · 1,0 - 1,2 mm · x2 · (red/orange) |