

# COMPACT EVO 406C



## FEATURES


## TECHNICAL DATA

Input Voltage
Power 60%
No load voltage $U_0$
Amp. Min-Max
Duty Cycle 40°
Insulation class
Protection degree
Dimensions (LxWxH)
Weight box/net

COMPACT EVO 406C	
400V ± 10% · 50/60 Hz · (3ph)	
MMA	TIG
13,7 KVA	12,2 KVA
75 V	10 V
5 ÷ 350 A	5 ÷ 400 A
350A @ 50%	400A @ 50%
270A @ 100%	300A @ 100%
H	
IP 22S	
255x530x460 mm	
31,5 / 30,1 kg	

## STANDARD CONFIGURATION

99815043A	COMPACT EVO 406C
-----------	------------------

## CUSTOMIZED CONFIGURATION

### ● MMA WELDING KIT

99900022	MMA Welding KIT · 50 mm <sup>2</sup> · 5+3 mt · conn. 50 mm <sup>2</sup>
99900063	MMA Welding KIT · 70 mm <sup>2</sup> · 5+3 mt · conn. 70 mm <sup>2</sup>

### ● GROUND CABLES

43210076K	Ground cable with clamp · 50 mm <sup>2</sup> · 3 mt · conn. 50 mm <sup>2</sup>
43210115K	Ground cable with clamp · 70 mm <sup>2</sup> · 3 mt · conn. 70 mm <sup>2</sup>
43210247K	Ground cable with C-clamp · 70 mm <sup>2</sup> · 5 mt · conn. 95 mm <sup>2</sup>

### ● WELDING TORCHES

43205037K	Welding cable with electrode holder · 50 mm <sup>2</sup> · 5 mt · conn. 50 mm <sup>2</sup>
43205052K	Welding cable with electrode holder · 70 mm <sup>2</sup> · 5 mt · conn. 70 mm <sup>2</sup>

23020176	TIG Torch · <b>EXPERTIG 26</b> · 4 mt · conn. 50 mm <sup>2</sup> · 12 Pin · Air · Consumables KIT Ø 2,4 mm
----------	--

### ● REMOTE CONTROL

99810020	Manual remote control · 12 pin · 10 mt	x MMA
----------	--	-------

### ● TROLLEYS

99900171A	Trolley · 2 wheels + shelves <b>ECO</b>	
99900258A	Trolley · 4 wheels + shelves <b>HD</b>	*(no H <sub>2</sub> O)