



TP 215

SYNERGIC



HELVI CONFIGURATION KIT

	TP 215
Generator	99820023
Electr. holder	43205098
MIG torch	23000425
Gas regulator	22905090
Earth clamp	43210132
Kit Code	99820023K

	TP 215		
	(1ph) 230V 50/60Hz		
Power 30%	5,5 KVA		
	MMA	TIG	MIG
U _o	65 V	65 V	35 V
Amp. Min-Max	5 ÷ 200 A	5 ÷ 200 A	20 ÷ 200 A
Amp. 60974-1	35% 200 A 100% 120 A	35% 200 A 100% 120 A	35% 200 A 100% 140 A
Aluminium	-	-	Ø 0,8 ÷ 12 mm
Steel	-	-	Ø 0,6 ÷ 12 mm
Flux core	-	-	Ø 0,8 ÷ 12 mm
Stainless Steel	-	-	Ø 0,8 ÷ 12 mm
Brazing	-	-	Ø 0,8 ÷ 12 mm
Ø E	1,6 ÷ 5 mm	-	-
Insulation	H		
Protec. degree	IP22S		
 (LxWxH)	770x450x660 mm		
 (LxWxH)	795x360x540 mm		
 box/net	51 / 48 Kg		
Code	99820023K		



TP 215

ENG • Microprocessor-controlled welding inverter suitable for DC controlled MIG/ MAG, TIG and STICK WELDING, which guarantees excellent stability of the welding arc and no welding spatters. In STICK mode, the microprocessor controls the Hot Start, Arc Force and Anti-sticking functions. In TIG mode, it controls the Lift Arc function and in MIG mode it allows either manual or fully synergic welding. Regulation of the slope-up motor, automatic soft start wire feed control of the arc. Its simplicity and versatility make it perfect for use in body shops, workshops and for all maintenance tasks. All of the functions can be easily selected on the front panel. Digital displays show the welding voltage and current and all the parameters selected. The TP 215 model is the wheel-based version and is fitted to accept reels with diameter of 300mm and 200mm.

IT • Inverter di saldatura, multifunzione MIG/MAG, TIG e STICK controllato a microprocessore, che garantisce un'eccezionale stabilità d'arco e una saldatura senza spruzzi. In posizione stick il microprocessore controlla le funzioni di Hotstart, Arc Force e anti-incollaggio, nella posizione TIG la funzione di lift arc e in modalità MIG dà la possibilità di saldatura manuale e sinergia totale. Regolazione della rampa di salita del motore, accostaggio automatico del filo per un innesco soft dell'arco. Per la sua semplicità e versatilità risulta ideale per l'utilizzo in carrozzeria, piccole carpenterie e lavori di manutenzione. Tutte le funzioni sono facilmente selezionabili sul pannello frontale. Sono presenti i display digitali per la visualizzazione di tensione e corrente di saldatura e dei vari parametri selezionati. Il modello TP215 è la versione carrellata. Permette l'utilizzo delle bobine di filo diametro 300 mm e ha il supporto bombola integrato.



TP
RANGE
MULTIPROCESS



ACCESSORIES INCLUDED

Generator 99820023

Electrode holder • 16 mm² • 3,0 meters

MIG torch 25 • 3,0 meters

Ground cable • 25 mm² • 3,0 meters

Gas regulator CO₂ Mini • 2 gauges

Adaptor for gas bottle CO₂ - Ar

EXTRA ACCESSORIES

21905073 Adjustable face shield • 2 sensors

21905086 HD welding gloves for MIG/MMA welding

23020159 TIG torch **Tig 17V** • 4 m • 50mm² • air cooled

23020154 TIG torch **Ergo Tig 17** • 4 m • 50mm² • air cooled